

Veneer Gypsum Board Product Description

Cabot Gypsum Veneer Board has a core of noncombustible, dimensionally stable gypsum rock sandwiched between a face layer of 100% recycled blue/gray colored paper and a brown back paper. The face paper is designed to absorb moisture and allow plaster products to adhere to the surface yet protect the core/paper bond. The face paper is formed along each long edge, and wrapped and sealed to the paper on the backside. This produces a strong yet flexible panel in convenient width and lengths. Even though Cabot Gypsum Veneer Board has some inherent fire resistant characteristics it is not intended for use in assemblies requiring a fire rating.

Cabot Gypsum Veneer Board can be used for most walls, partitions and ceilings in both new commercial and residential construction and remodeling work.

Cabot Gypsum Veneer Board is an excellent barrier to the transmission of noise and thermal energies but must be installed in the proper thickness and methods that has been tested to achieve the desired rating as per Standard Specification for Application and Finishing of Gypsum Board, ASTM C 840, non rated construction.

Product Limitations

1. Exposure to excessive or continuous moisture and extreme temperature 52° C (125° F) should be avoided.
2. Store indoors and off ground surface.
3. Boards should be stacked flat with care taken to prevent sagging or damage to edges, ends and surfaces.
4. Storing board lengthwise leaning against framing is not recommended.
5. This board is nonstructural and should not be used as a nailing base to support heavy wall-mounted objects
6. Cabot Gypsum Veneer Board should only be used with veneer plaster products.

Product Data

Surface Burning Characteristics: Flame Spread Rating of 15, Smoke Developed 0 per ASTM E 84 or CAN/ULC-S102
Thickness: ½" (12.7 mm)
Width: 4' (1220 mm)
Lengths: 8' (2440 mm) to 12' (3660 mm)*
Edges: Tapered, Square
Packaging: Two pieces per bundle, face-to-face and end taped.

*Special lengths may be available, consult nearest Cabot Gypsum sales office.

Product Application

Cabot Gypsum Veneer Board can be applied to wood framing with drywall nails or Type W screws and with special adhesives in combination with supplemental fasteners. The Veneer Board may also be applied to light gauge metal framing with self-tapping Type S screws. The application must conform to ASTM C 844, Application of Gypsum Base to Receive Gypsum Veneer Plaster. The board can be cut to size using the standard score and snap method to create tight fitting joints. In cold weather or during joint finishing, temperatures within the enclosure should stay within the range of 50° to 95°F (10° to 35°C) and with sufficient ventilation to carry off excess moisture.

Board Decoration

Cabot Gypsum Veneer Board comes from the factory ready-to-use, the plaster products are by others. Both the veneer plaster manufacturer's recommendations and those of ASTM C 843, Application of Gypsum Veneer Plaster must be adhered to.

Product Specification

Cabot Gypsum Veneer Board is manufactured to meet or exceed the requirements of ASTM C1396 and CAN/CSA A82.27.

Cabot Gypsum Company

221 Henry Paint Street
Point Tupper
Nova Scotia
B9A 1Y8
Tel (902) 625-4547
Fax (902) 625-4540
Toll Free
1-855-625-4547
cabotgypsum.com



The specifications herein contain the best information we have relating to our products and the recommended uses of our products are based on tests believed to be reliable. These specifications supersede all previous issues and are subject to change without notice.

Limited Warranty

Cabot Gypsum expressly warrants the products described herein to be free from defects at the time of shipment. Except for such express warranties, Cabot Gypsum makes no warranty, express or implied, and all warranties of merchantability, fitness for a particular purpose, and other warranties are disclaimed and excluded by Cabot Gypsum. Except for the breach of such express warranties, Cabot Gypsum shall not, under any circumstances, be liable for any imperfection, deviation from specifications or other defect impairing the quality, value or suitability of any product. In no event shall Cabot Gypsum be liable for consequential, special or contingent damages or other claims or demands, except to the extent of the purchase price of the product, the refund of which shall be the purchaser's exclusive remedy. Any claims by purchaser for defective products must be made in writing within 30 days after the purchaser's receipt of shipment and in all events before installation is commenced. Cabot Gypsum shall have the right at its option to replace or repair any defective products, to refund the purchase price or to grant a reasonable allowance on account of such defects.